

References

- Akhtar, M.S., B.K. Richards, P.A. Medrano, M. deGroot and T.S. Steenhuis. 2003. Dissolved Phosphorus from Undisturbed Soil Cores: Related to Adsorption Strength, Flow Rate, or Soil Structure? *Soil Sci. Soc. Am. J.* 67:458–470.
- Anderson, James R., Hardy, Ernest E., Roach, John T., Witmer, Richard E., 1976, “A Land Use and Land Cover Classification for Use with Remote Sensing Data”, USGS Professional Paper 964, U.S. Department of the Interior, 28 pgs.
- Bode, R.W., M. A. Nowak, L. E. Abele, D. L. Heitzman, S. I. Passy. 2001. Biological Stream Assessment, West Branch Delaware River, Delaware County, New York. New York State Department of Environmental Conservation, Albany. 44pp.
- Cadwell, D.H. 1986. "Late Wisconsinan stratigraphy of the Catskill Mountains", in, Cadwell, D.H., ed. *The Wisconsinan Stage of the first geological district, eastern New York*. New York State Museum Bulletin 455.
- Day, Laurence, Richard Weidenbach, 1990. *Aquifer Characteristics and Parameters of the West Branch of the Delaware Valley Between Walton and Hamden*. Delaware County Soil and Water Conservation District. Walton, NY.
- Dineen, Robert J. 1986. "Deglaciation of the Hudson Valley Between Hyde Park and Albany, NY", in D. H. Cadwell, ed., *The Wisconsinan Stage of the First Geological District, Eastern, NY*. New York State Museum, Bulletin No. 455.
- Fletcher, 1967. "Middle and Upper Devonian clastics of the Catskill Front, New York." *N.Y. State Geological Association Guidebook 39*, New Paltz, p. C1-23.
- Frankenberger, J.R. 1996. Identification of critical runoff generating areas using a variable source area model. PhD. Thesis, Dept. Ag. Biol. Eng. Cornell U., Ithaca, NY 207 pp.
- Frankenberger, J.R., E.S. Brooks, M.T. Walter, M.F. Walter and T.S. Steenhuis. 1999. A GIS-based variable source area hydrology model. *Hydro. Proc.* 13:805-822.
- Geohring, L.D., T.S. Steenhuis, M.T. Walter, M.F. Walter, Q.M. Ketterings and K.J. Czymmek. 2002. Phosphorus risk assessment tools for New York State. In: *Proceedings of the 2002 ASAE Annual Meeting, Chicago, IL, July 28-31, 2002*. Amer. Soc. Agric. Eng., St. Joseph, MI.
- Hey, R. D. 2003, *Natural Rivers: Mechanisms, Morphology and Management*, Wildland Hydrology, Pagosa Springs, CO. p5-1.

Isachsen Y.W., E. Landing, J.M. Lauber, L.V. Rickard and W.B. Rogers (eds.) 1991. Geology of New York: A simplified account. Educational Leaflet 28. New York State Museum, Albany, NY.

Knighton, David 1998. Fluvial Forms and Processes A New Perspective, Arnold, London.

Kudish, Michael, (2000), The Catskill Forest: A History, Purple Mountain Press, Ltd. Fleischmanns, NY., pp. 217.

Leopold Luna B, 1997. Waters, Rivers, and Creeks, University Science Books, Sausalito, CA. p105.

Lumia, R. 1991. Regionalization of Flood Discharges for Rural, Unregulated Streams in New York, Excluding Long Island. USGS Water-Res. Inv. Rpt. 90-4197. Albany, NY. 119 pp.

Lumia, R. 1998. Flood of January 19-20, 1996 in New York State. USGS Water-Resources Investigations Report 97-4252. USGS, Albany, NY

Malanson, George P., 1993, Riparian Landscapes, Cambridge University Press, Cambridge, UK.p. 198.

McCormack, D., K. Young and G. Darby. Rock Fragments and the K Factor of the Universal Soil Loss Equation. 1984. *In*: Erosion and Productivity of Soils Containing Rock Fragments. Soil Science Society of America -- Special publication #13, pp. 73-81.

Miller, S.J. and D. Davis, 2002. Identifying and Optimizing Regional Relationships for Bankfull Discharge and Hydraulic Geometry at USGS Stream Gage Sites in the Catskill Mountains, NY NYCDEP Provisional Report. pp. 31

New York Natural Heritage Program, 2002, "Ecological Communities of New York State", Draft of 2nd Edition, N.Y.S. Department of Environmental Protection, Albany, NY. pp. 134

NOAA 2002. Climatology of the United States No. 81, Monthly Station Normals of Temperature, Precipitation, and Heating and Cooling Degree Days 1971-2000, 30 New York. NESDIS/NOAA. Asheville, NC.

Reporter Company, The, 1996. Disaster Along The Delaware River. Walton, NY

Rich, J.L. 1935. Glacial Geology of the Catskills. New York State Museum Bulletin 299, 180 p.

Rickard, 1975. Correlation of the Silurian and Devonian rocks in New York State. New York State Museum, Geological Survey Map and Chart Series, no. 24

- Ritter, Dale. 1978. Process Geomorphology. W.C. Brown Co., Dubuque, IA. p236.
- Rosgen, D.L. 1996. Applied River Morphology. Wildland Hydrology, Pagosa Springs, CO.
- Rosgen, D. L. 2001. River Restoration and Natural Channel Design, Wildland Hydrology, Pagosa Springs, CO. pA-40.
- Rubin, Paul 1997. "Geotechnical and Hydrogeologic Factors Affecting Bank and Bottom Stability Adjacent to and in Catskill Mountain Stream Channels; With Design Considerations for Broadstreet Hollow". NYCDEP Internal Memorandum.
- Soren, J. 1963. The Ground-Water Resources of Delaware County, New York. USGS Bulletin GW-50. Albany. 59 pp.
- Sanford, D. K. 1989. Report of Creel Census and Population Estimates in the West Branch of the Delaware River Between South Kortright and Delhi 1984 – 1986. New York State Department of Environmental Conservation, Stamford. 16 pp. Plus appendices.
- Simon, A. and C.R. Hupp. 1992. Geomorphic and Vegetative Recovery Processes Along Modified Stream Channels of West Tennessee. U.S. Geological Survey, Open File Report 91-502.
- Strahler, A. N. 1964 Quantitative geomorphology of drainage basins and networks. In: Chow, V. T. (ed) Handbook of Applied Hydrology. McGraw_Hill, New York.
- Thaler, J.S. 1996. Catskill Weather. Purple Mountain Press, Fleischmanns, NY
- Thorne, C. R., R. D. Hey, M. D. Newson eds, Applied Fluvial Geomorphology for River Engineering and Management, John Wiley and Sons, Chichester, England, p316.
- Titus, Robert 1996. The Catskills in the Ice Age. Purple Mountain Press. 123 pp.
- Williams, Charles E., Moriarity, William J. 1999. "Composition and Structure of Hemlock-Dominated Riparian Forests of the Northern Allegheny Plateau: A Baseline Assessment", Proceedings: Symposium on Sustainable Management of Hemlock Ecosystems in Eastern North America, US Forest Service, General Technical Bulletin NE-267, pgs 216-224.

Glossary of Terms

Note: where a word within a definition is italicized, it is defined elsewhere within the glossary

aggradation (aggrading) – A progressive build-up or raising of the channel bed and *floodplain* due to *sediment* deposition. The geologic process by which streambeds are raised in elevation and *floodplains* are formed. Aggradation indicates that stream *discharge* and/or *bedload* characteristics are changing.

aquatic habitat – Physical attributes of the stream channel and *riparian area* that are important to the health of all or some life stages of fish, aquatic insects and other stream organisms. Attributes include water quality (temperature, pH), *riparian* vegetation characteristics (shade, cover, density, species), stream bed *sediment* characteristics, and *pool/riffle* spacing.

Bank Erodibility Hazard Index (BEHI) – An index for predicting *erosion potential* on selected streambanks, usually associated with a *monitoring cross-section* for measurement of actual *erosion* rates over time (Rosgen, 1996).

bankfull depth – The depth from the elevation of water surface at the *bankfull discharge* to the deepest point in the channel.

bankfull discharge – The discharge (or flow) that occurs, on average, every 1.2 to 2.0 years. This discharge, from relatively frequent storms, is largely responsible for the shape of the stream channel within the *floodplain*.

bankfull width – The width of the water surface at the *bankfull discharge*.

base flood elevation – The height of the base flood, usually in feet, in relation to the National Geodetic Vertical Datum of 1929, the North American Vertical Datum of 1988, or other datum referenced in the Flood Insurance Study report, or average depth of the base flood, above the ground surface.

bedload – *Sediment* moving on or near the streambed and transported by jumping, rolling or sliding on the bed layer of a stream.

berm – A mound of earth or other materials, usually linear, constructed along streams, roads, *embankments* or other areas. Berms are often constructed to protect land from flooding or eroding, or to control water drainage (as along a road-side ditch). Some berms are constructed as a byproduct of a stream management practice whereby stream bed *sediment* is pushed out of the channel and mounded on (and along the length of) the stream bank - these berms may or may not be constructed for flood control purposes; some are simply piles of excess material. These berms often interfere with other stream processes such as *floodplain* function, and can exacerbate flood-related *erosion* or stream *instability*.

boulder – In the context of *stream assessment surveys*, a boulder is stream *sediment* that measures between 256 mm and 4096 mm (about 10 inches to 13.3 feet).

braided – A stream form in which the channel splits into 3 or more separate sub-channels, often criss-crossing to produce a “braided” pattern of connected channel with large or small islands between them. Islands formed between the channels can be either bare *gravel* or *cobble* materials, or contain mature forest vegetation.

channel-forming flow – see *bankfull discharge*

clay, clay exposure (see also glacial lake clay) – Clay is the smallest *sediment* size present in a stream, measuring less than 0.0039mm in size. Clay can be identified by its smooth and slippery texture. Clay deposits can be seen in sections of the stream, and can produce *turbidity* in stream water when it is disturbed either during floods or by activity in the stream. For a detailed description of ‘*glacial lake clay*,’ see Chapter 3.1.1, Geology.

cobble – In the context of *stream assessment surveys*, cobble material is *sediment* that measures between 64 mm and 256 mm (about 2.5 inches to 10 inches).

cohesive - Soil types such as *clays* and *silts* that are held together owing to attraction between like molecules.

confluence – The location of the joining of two separate streams, each with its own *watershed*.

cross-section (see also monitoring cross-section) – In the context of *stream assessment surveys*, a *cross-section* is a location on a stream channel where stream *morphology* is measured perpendicular to the *stream flow* direction (as if taking a slice through the stream), including width, depth, height of banks and/or *terraces*, and area of flow.

culvert – A closed conduit for the free passage of surface drainage water³. Culverts are typically used by the Town and County to control water running along and under the road, and to provide a crossing point for water from road side drainage ditches to the stream, as well as for routing *tributary* streams under the roads. Culverts are also used by landowners to route roadside drainage ditch water under their driveways to reduce or prevent *erosion*.

degradation (degrading) – The process by which a stream *reach* or channel becomes deeper by eroding downward into its bed over time, also called “downcutting”, either by periodic episodes of bed scouring without filling, or by longer term transport of *sediment* out of a *reach* without replacement.

demonstration stream restoration project, (demonstration project) – A *stream (stability) restoration* project that is designed and located to maximize opportunities for *monitoring* of project success, public and agency education about different *stream restoration* techniques, and interagency partnerships for funding and cooperation.

destabilized (see also instability, unstable) – Describing a section of stream that has been made *unstable*, by natural or human activity.

discharge (stream flow) – The amount of water flowing in a stream, measured as a volume per unit time, usually cubic feet per second (cfs).

embankment – A linear structure, usually of earth or *gravel*, constructed so as to extend above the natural ground surface³. Similar to a *berm*, but usually associated with *road fill* areas, and extending up the hillside from the road, or from the stream up to the road surface.

entrenched – In stream classification (see *stream type*), entrenchment (or entrenchment ratio) is defined by stream *cross-sectional* shape in relation to its *floodplain* and valley shape, and has a specific numerical value that in part determines *stream type*. For example, if this number is less than 1.4, the stream is said to be highly entrenched, if between 1.4 and 2.2 it is mildly entrenched, and greater than 2.2 it is not entrenched. Entrenchment ratio is used with other stream shape data to determine *stream type*, and define baseline data for future *monitoring* (Rosgen, 1996).

equilibrium (see also “stable”) – The degree to which a stream has achieved a balance in transporting its water and *sediment* loads over time without *aggrading* (building up), *degrading* (cutting down), or migrating laterally (eroding its banks and changing course).

erosion – The wearing away, detachment, and movement of the land surface (*sediment*), by running water, wind, ice, or other geological agents, including such processes as gravitational creep or *slumping*.¹ In streams, erosion is a natural process, but can be accelerated by poor stream management practices.

erosion potential – The amount of *erosion* that may be expected under given climatic, topographic, soil, and cultural conditions.¹

exotic plant – see *invasive plants*

floodplain – The portion of a river valley, adjacent to river channel, which is covered with water when river overflows its banks at flood *stage*. The floodplain usually consists of *sediment* deposited by the stream, in addition to *riparian* vegetation.⁴ The floodplain acts to reduce the *velocity* of floodwaters, increase infiltration (water sinking into the ground rather than running straight to the stream - this reduces the height of the flood for downstream areas), reduce stream bank *erosion* and encourage deposition of *sediment*. Vegetation on floodplains greatly improves their functions.

floodstage – The *stage* at which overflow of the natural banks of a stream occurs.

gabions – Large wire-mesh baskets filled with rock material used to *harden* or *stabilize* road *embankments* and sometimes stream banks.

Geographic Information System (GIS) – Desktop software with a graphical user interface that allows loading and querying, analysis and presentation of spatial and tabular data that can be displayed as maps, tables and charts.⁵ The maps in the West Branch Delaware stream

management plan were produced with a GIS, and can be updated as new information becomes available.

Global Positioning System (GPS) – A satellite-based positioning system operated by the U.S. Department of Defense (DoD). When fully deployed, GPS will provide all-weather, worldwide, 24-hour position and time information.⁶ The *stream assessment survey* done for the West Branch Delaware stream management plan included the use of a GPS unit to document the locations of all mapped stream features. This information was added to the *GIS* to produce the maps.

gravel – In the context of *stream assessment survey*, *gravel* is *sediment* that measures between 2 mm and 64 mm (about 0.08 inches to 2.5 inches).

hardening – Any structural *revetment* that fixes in place an eroding stream bank, *embankment* or hillside by using “hard” materials, such as rock, sheet piling or concrete, that does not allow for revegetation or enhancement of *aquatic habitat*. *Rip-rap* and *stacked rock walls* are typically considered to be hardening measures, though some revegetation of these areas is possible.

head-cut – A marked change in stream bed slope, as in a “step” or waterfall, that is unprotected or of greater height than the stream can maintain. This location, also referred to as a “knick point”, moves upstream, eventually reaching an *equilibrium* slope.

instability (see also “unstable”) – An imbalance in a stream’s capacity to transport *sediment* and maintain its channel shape, pattern and profile.

incised – *Erosion* of the channel by the process of *degradation* to a lower base level than existed previously or is consistent with the current hydrology.

invasive plants – Species that are not native to a region or country that have the ability to compete with and replace native species in natural habitats, also referred to as “exotic” plants. (Erich Haber, *Impact of Invasive Plants*, 2002).

Japanese Knotweed (see also invasive plants) – An *invasive plant*, not native to the Catskill region, that colonizes disturbed or wet areas, especially stream banks, road-side ditches and *floodplains*. This plant out-competes natives and other beneficial plants, and may contribute to *unstable* stream conditions.

left bank – The left stream bank as looking or navigating downstream. This is a standard used in *stream assessment surveys*.

matrix – The framework material within which other materials are lodged or included. For example, *cobbles* could be embedded in a matrix of *sand* and fine *gravel*.

meander – Refers both to a location on a stream channel that is curved (a “meander bend”), and to the process by which a stream curves as it passes through the landscape (a “meandering stream”).

monitoring – The practice of taking similar measurements at the same site, or under the same conditions, to document changes over time.

monitoring cross-section – For the purposes of the West Branch Delaware stream management plan, this is a location where metal rebar rods have been used to permanently locate an actively eroding stream bank. At this site, detailed data have been gathered to document the stream condition. The site is permanently marked to enable future measurements that, when compared to the existing condition, provide information about the stream's change. Measuring change over time is considered '*monitoring*,' and this information provides early warning to stream managers about important but perhaps visually imperceptible changes in the stream.

monumented – Refers to a location, usually a *cross-section*, that is marked with a permanent or semi-permanent marker, or "monument", to enable future *monitoring* at the same place.

morphology, stream morphology – The physical shape, or form, of a landscape or stream channel, that can be measured and used to analyze stream or landscape condition, type or behavior.

nutrient – The term "nutrients" refers broadly to those chemical elements essential to life on earth, but more specifically to nitrogen and phosphorus in a water pollution context. In a water quality sense nutrients really deals with those elements that are necessary for plant growth, but are likely to be **limiting** -- that is, where used up or absent, plant growth stops.

Pfankuch assessment – a stream channel *stability* evaluation procedure that assesses a number of stream channel and streambank conditions to derive a numerical rating for stream *reach* condition.

pool – A small section of stream characterized by having a flat or nearly flat water surface compared to the average *reach* slope (at low flow), and deep and often asymmetrical *cross-sectional* shape.

reach – A section of stream with consistent or distinctive *morphological* characteristics¹.

reference reach, stable reference reach – A *stable* portion of a stream that is used to model restoration on an *unstable* portion of stream. Stream *morphology* in the reference reach is documented in detail, and that *morphology* is used as a blueprint for design of a *stream stability restoration* project.

revetment – Any structural measure undertaken to stabilize a road *embankment*, stream bank or hillside.

riffle – A small section of stream characterized by having a steep water surface slope compared to the average *reach* slope (at low flow), and a shallow and often uniform *cross-sectional* shape.

right bank – The right stream bank as looking or navigating downstream. This is a standard used in *stream assessment surveys*.

riparian (area, buffer, vegetation, zone) – The area of land along stream channels, within the valley walls, where vegetation and other land uses directly influence stream processes, including flooding behavior, *erosion*, *aquatic habitat* condition, and certain water quality parameters.

rip-rap – Broken rock, *cobbles*, or *boulders* placed on earth surfaces, such as a road *embankment* or the bank of a stream, for protection against the action of water; materials used for soil *erosion* control.¹

rotational failure (translational failure) – A geotechnical term referring to the shape and mechanism of a hillslope failure that results in a section of land surface that falls, or “fails”, by rotating out of place along a curved plane surface (as opposed to sliding along a straight line or flat plane surface). This type of failure is common in the West Branch Delaware valley, easily recognized by “back leaning” trees on displaced sections of the slope, separated by fault scarps (cracks in the ground surface perpendicular to the failure direction, also often curved) as these blocks of land rotate downward and outward.

runoff – The portion of precipitation (i.e., rainfall) that reaches the stream channel over the land surface.

sand – In the context of *stream assessment surveys*, sand material is *sediment* that measures between 0.063 mm and 2 mm (up to 0.08 inches).

sediment, stream bed sediment – Material such as *clay*, *sand*, *gravel* and *cobble* that is transported by water from the place of origin (stream banks or hillsides) to the place of deposition (in the stream bed or on the *floodplain*).³

sediment discharge – The combination of *washload* plus *bedload* material.

silt – In the context of *stream assessment surveys*, silt material is *sediment* that measures between 0.0039 mm and 0.063 mm.

sinuosity – The ratio of channel length to direct down-valley distance. Also may be expressed as the ratio of down-valley slope to channel slope.

slump – The product or process of mass-wasting when a portion of hillslope slips or collapses downslope, with a backward rotation (also a rotational failure).

stable (see also equilibrium) – A stable stream is defined as maintaining the capacity to transport water and *sediment* loads over time without *aggrading* (building up), *degrading* (cutting down), or migrating laterally (eroding its banks and changing course). Stable streams resist flood damage and *erosion*, and provide beneficial *aquatic habitat* and good water quality for the particular setting.

stability – In stream channels, the relative condition of the stream on a continuum between *stable* (in *equilibrium* or balance) and *unstable* (out of *equilibrium* or balance). Stream stability assessment seeks to quantify the relative *stability* of stream *reaches*, and can be used to rank or prioritize sections of streams for management.

stacked rock wall – A *boulder revetment* used to line stream banks for stabilization. Stacked rock walls can be constructed on a steeper angle than *rip-rap*, so they take up less of the stream *cross-section*, provide a wider road surface, and provide less surface area for solar heating, allowing stream temperature to remain cooler relative to banks lined with *rip-rap*. These features can be augmented with bioengineering to enhance *aquatic habitat* and *stability* functions.

stage – In streams, stage refers to the level or height of the water surface, either at the current condition (i.e., current stage), or referring to another specific water level (i.e., flood stage).

stream assessment, stream assessment survey – The methods and summary information gathered in a stream *reach* or series of *reaches*, primarily focused on stream *morphology*. Stream assessment for the West Branch Delaware included detailed characterization and mapping of stream channel patterns, *cross-section* shapes and slope.

stream flow (discharge) – The amount of water flowing in a stream, measured as a volume per unit time, usually cubic feet per second (cfs).

stream stability restoration (design, project) – An *unstable* portion of stream that has been reconstructed, using *morphology* characteristics obtained from a *stable reference reach* in a similar valley setting, that returns the stream to a *stable* form (that is, to a shape that may allow the stream to transport its water and *sediment* load over time without dramatic changes in its overall shape).

stream type – As defined by Rosgen (1996), one of several categories defined in a stream classification system, based on a set of delineative criteria in which measurements of channel parameters are used to group similar *reaches*.

terrace – A level area in a stream valley, above the active *floodplain*, that was deposited by the stream but has been abandoned as the stream has cut downward into the landscape. These areas may be inundated (submerged) in higher floods, but are typically not at risk in more common floods.

thalweg – The line followed by the majority of the *stream flow*.¹ In *stream assessment*, this location is used as a reference location for surveys and other measurements, and is most often associated with the deepest point in the stream *cross-section* (i.e., the stream channel that would still have water flowing in it at even the lowest flow conditions).

toe – The bottom, or base, of a stream bank or *embankment*.

tributary – A stream that feeds into another stream; usually the tributary is smaller in size than the main stream (also called “mainstem”). The location of the joining of the two streams is the *confluence*.

turbidity – A measure of opacity of a substance; the degree to which light is scattered or absorbed by a fluid. Streams with high turbidity are often referred to as being “turbid”.

unstable (see also instability) – Describing a stream that is out of balance in its capacity to transport *sediment* and maintain its channel shape, pattern and profile over time.

washload – The finest-grained fraction of the total *sediment* load, consisting of particles whose settling *velocity* are so low that they are transported in suspension at approximately the same speed as the flow and only settle out when flow *velocity* are much reduced.

watershed – A unit of land on which all the water that falls (or emanates from springs) collects by gravity and runs off via a common outlet (stream).²

wetland – An area that is saturated by surface water or ground water with vegetation adapted for life under those soil conditions, as in swamps, bogs, fens, and marshes.

velocity – In streams, the speed at which water is flowing, usually measured in feet per second.

¹New York Guidelines for Urban Erosion and Sediment Control, USDA SCS, 1972

²Black, P., Watershed Hydrology, 1991, Prentice-Hall Inc., Englewood Cliffs, NJ

³Lo, S. 1992. Glossary of Hydrology. Water Resourced Publications, PO Box 2841, Littleton, CO. 80161

⁴Rosgen, D.L. 1996. Applied River Morphology.

⁵ArcView *GIS*: The Geographic Information System for Everyone. Environmental Systems Research Institute, Inc. 1996.

⁶GPS Pathfinder Office: Getting Started Guide. Trimble Navigation Limited. 1999.

